







R o H S


REV.	ECN NO.	LOCAS.	DESCRIPTION	DATE	DESIGN
A			NEW DRAWING	22.12.01	Jenply



PC BOARD LAYOUT



SECTION A-A



PROPER CABLE (SCALE 2:1)

孔位	A	B	C	D
2	1.00	3.10	6.85	8.15
3	2.00	4.10	7.85	9.15
4	3.00	5.10	8.85	10.15
5	4.00	6.10	9.85	11.15
6	5.00	7.10	10.85	12.15
7	6.00	8.10	11.85	13.15
8	7.00	9.10	12.85	14.15
9	8.00	10.10	13.85	15.15
10	9.00	11.10	14.85	16.15
11	10.00	12.10	15.85	17.15
12	11.00	13.10	16.85	18.15
13	12.00	14.10	17.85	19.15
14	13.00	15.10	18.85	20.15
15	14.00	16.10	19.85	21.15
16	15.00	17.10	20.85	22.15
17	16.00	18.10	21.85	23.15
18	17.00	19.10	22.85	24.15
19	18.00	20.10	23.85	25.15
20	19.00	21.10	24.85	26.15
21	20.00	22.10	25.85	27.15
22	21.00	23.10	26.85	28.15
23	22.00	24.10	27.85	29.15
24	23.00	25.10	28.85	30.15
25	24.00	26.10	29.85	31.15
26	25.00	27.10	30.85	32.15
27	26.00	28.10	31.85	33.15
28	27.00	29.10	32.85	34.15
29	28.00	30.10	33.85	35.15
30	29.00	31.10	34.85	36.15

技术要求(Technical Index):

- 材质与表面处理(Material And Finish):
基座 (Housing) and 盖子 (Cover): LCP UL94V-0 Nature Or Black;
端子 (Terminal) :Phosphor Copper Au/Sn Plated;
焊片 (Solder): Copper Alloy Au/Sn Plated;
- 工作温度(Temperature range): -25° C~+85° C.
- 额定电压(Rated voltage): 50V, AC/DC.
- 额定电流: 0.5A, AC/DC.
- 接触电阻(Contact resistance): ≤20mΩ.
- 绝缘电阻(Insulation resistance): ≥800MΩ.
- 耐电压(Withstanding Voltage):500V AC/minute.

DESIGN:	Jenply	QWYCONN® 深圳市启崴源电子有限公司 SHENZHEN QIWEIYUAN ELECTRONIC CO.,LTD.			
CHECK:	Ke Tian	TITLE: 1.0mm FPC (A型) 下接(H=2.0)			
APPROVED:	Youquan Xu				
DIM	TOL	DIM	TOL	PART NO. 1.0K-MX-nPWB-***	
X.	±0.25	X°.	±3.0°		
X.X	±0.20	X.X°		REV. A	SCALE: N/A
X.XX	±0.15	X.XX°			
X.XXX		X.XXX°			
		UNIT:	mm	SHEET:	1/1